

PPF SLIP/TACK SOLUTION SUMMARY



	SLIP SOLUTION Neutral pH baby shampoo in ml per 1 Litre of distilled water		TACK SOLUTION 99.9% Isopropyl alcohol (IPA) In % of 1 Litre of distilled water	
	At 18-21°C room temperature	In warmer conditions	At 18-21°C room temperature	In warmer conditions
ULTRA CLEAR PRO (UCP)	2.5 to 4 ml	4 to 8 ml	20%	N/A
ULTRA CLEAR PRO 183cm	2.5 to 4 ml	4 to 8 ml	20%	N/A
LUCENT	1.5 to 3 ml	3 to 6 ml	10 - 20%	N/A
CARBON (GLOSS & MATTE)	2.5 to 4 ml	4 to 8 ml	20%	N/A
NITRO	2.5 to 4 ml	4 to 8 ml	10 - 20%	N/A
SATIN	2.5 to 4 ml	4 to 8 ml	20%	N/A
MATTE	1.5 to 3 ml	3 to 6 ml	10 - 20%	N/A
FROZEN	1.5 to 3 ml	3 to 6 ml	20%	N/A
BLACK SHINE	1.5 to 3 ml	3 to 6 ml	20%	N/A
MATTE BLACK	1.5 to 3 ml	3 to 6 ml	20%	N/A
PROCOLOR	2.5 to 4 ml	4 to 8 ml	20%	N/A
SOLID	1.5 to 3 ml	4 to 8 ml	20%	N/A
EXW75 Windscreen Protection	2.5 to 4 ml	4 to 8 ml	20%	N/A
SUNROOF PPF	2.5 to 4 ml	4 to 8 ml	20%	N/A
TOUCHSCREEN	Light mist of 1ml / Litre		Not applicable	

NOTE: these are guidelines only and local specific conditions as well as personal preference may require slight variations on the above recommendations. In doubt, always consult with your Profilm technical advisor or sales representative. Information on installation guidelines, warranty, as well as care & maintenance is available on <https://profilmgrp.com>