

PPF SLIP/TACK SOLUTION SUMMARY

Profilm™

| | SLIP SOLUTION Neutral pH baby shampoo in ml per 1 Litre of distilled water | | TACK SOLUTION 99.9% Isopropyl alcohol (IPA) In % of 1 Litre of distilled water | |
|-----------------------------|---|----------------------|---|----------------------|
| | At 18-21°C room temperature | In warmer conditions | At 18-21°C room temperature | In warmer conditions |
| ULTRA CLEAR PRO (UCP) | 3 ml | 5 ml | 20% | N/A |
| ULTRA CLEAR PRO 183cm | 3 to 4 ml | 5 to 7 ml | 20% | N/A |
| ULTRA CLEAR PRO. | 6 to 7 ml | up to 10 ml | 20% | N/A |
| reGen | 3 ml | 5 ml | 20% | N/A |
| CARBON (GLOSS & MATTE) | 3 to 5 ml | 7 to 15 ml | 20% | N/A |
| HYDROPROTECT | 3 to 4 ml | up to 10 ml | 20% | N/A |
| NITRO | 3 to 5 ml | up to 10 ml | 10 - 20% | N/A |
| SATIN MATTE | 3 ml | 5 ml | 20% | N/A |
| SUPER MATTE | 3 to 5 ml | 6 to 10 ml | 10 - 20% | N/A |
| NITRO MATTE | to be confirmed | to be confirmed | 20% | N/A |
| BLACK SHINE | 3 to 5 ml | 6 to 10 ml | 20% | N/A |
| MATTE BLACK | 3 to 5 ml | 6 to 10 ml | 20% | N/A |
| PROCOLOR | 6 to 10 ml | 10 to 15 ml | 20% | N/A |
| SOLID | 3 to 5 ml | 7 to 15 ml | 20% | N/A |
| EXW75 Windscreen Protection | 6 to 8 ml | 6 to 12 ml | 20% | N/A |
| SUNROOF PPF | 6 to 8 ml | 10 to 12 ml | 20% | N/A |
| TOUCHSCREEN | Light mist of 1ml / Litre | | Not applicable | |

NOTE: these are guidelines only and local specific conditions as well as personal preference may require slight variations on the above recommendations. In doubt, always consult with your Profilm technical advisor or sales representative. Information on installation guidelines, warranty, as well as care & maintenance is available on <https://profilmgrp.com/paint-protection-film/>